

SAFETY DATA SHEET



DATE ISSUED :	5/21/2016
SDS REF. No :	S1600-01

1600-01 POLY FAST REDUCER

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: 1600-01 POLY FAST REDUCER

PRODUCT CODE: S1600-01

PRODUCT USE: Industrial Solventborne Blend

MANUFACTURER

Cardinal Industrial Finishes
1329 Potrero Ave

S. El Monte, CA,
626 444-9274

24 HR. EMERGENCY TELEPHONE NUMBER

CHEMTREC (US Transportation): (800)424-9300

CHEMTREC (International : 1(202)483-7616

Transportation)

WEB: WWW.CARDINALPAINT.COM

2. HAZARDS IDENTIFICATION

PICTOGRAMS



SIGNAL WORD : DANGER

HAZARD STATEMENTS :

H226 Flammable liquid and vapor.

H302 Harmful if swallowed.

H320 Causes serious eye irritation.

H315 Causes serious eye irritation.

PRECAUTIONARY STATEMENTS :

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P264 Wash thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/.../equipment.

P243 Take precautionary measures against static discharge.

P270 Do not eat, drink or smoke when using this product.

P302 + P352 IF ON SKIN: Wash with plenty of water.

P363 Wash contaminated clothing before reuse.

P405 Store locked up.

P501 Dispose of in accordance with Local, Regional, State, Federal, and International Regulations.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	Weight %	CAS Number	
n-Butyl Acetate	60% - 65%	123-86-4	

Methyl Ethyl Ketone	35% - 40%	78-93-3	
---------------------	-----------	---------	--

4. FIRST AID MEASURES

Description of first aid measures.

EYES CONTACT : Flush with large quantities of water for 15 to 30 minutes. Remove contact lenses. Keep eyes wide open while rising. If eye irritation persists: Get medical attention.

SKIN CONTACT : Wash exposed area with mild soap and water for 15 to 30 minutes. Remove contaminated clothing. Repeated exposure may cause dryness or cracking.

INGESTION : Rinse mouth. Do NOT induce vomiting. Keep victim warm and seek immediate attention.

INHALATION : Remove to fresh air and keep in a position comfortable to breath. Call a doctor/physician if you feel unwell. Get medical attention.

Most important symptoms and effects, both acute and delayed. Symptoms/injuries: Eye irritation

Symptoms/injuries after inhalation: May cause drowsiness or dizziness.

Symptoms/injuries after eye contact: Cause serious eye irritation.

Symptoms/injuries after ingestion: Ingestion may cause nausea, vomiting and diarrhea.

Indication of any immediate medical attention and special treatment needed.

If medical advise is needed, have product container or label on hand.

5. FIRE FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA : In the event of a fire, use specifically suitable extinguishing agents. Suitable extinguishing media: Foam, alcohol resistant foam, CO₂, water fog. Unsuitable extinguishing media: Do not use heavy water stream. A heavy water stream may spread burning liquid.

FIRE FIGHTING PROCEDURE : Firefighting instructions: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering the environment.

Protection during firefighting: Firefighters should wear full protective gear. Do not enter fire area without proper protective equipment, including self-contained breathing apparatus with full face piece operated in pressure demand or other positive pressure modes.

UNUSUAL FIRE AND EXPLOSION HAZARD : Fire hazard: Highly flammable/liquid or vapor.

Explosive hazard: May form flammable/explosive vapor-air mixture.

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES :

General measures: Remove ignition sources. Use special care to avoid static electric charges. No smoking.

FOR NON-EMERGENCY PERSONNEL :

For non-Emergency procedures: Evacuate unnecessary personnel.

FOR EMERGENCY RESPONDERS :

Equip cleanup crew with proper protection. Avoid breathing fume, vapors.

ENVIRONMENTAL PRECAUTIONS :

Prevent entry to sewers and public waters.

METHODS AND MATERIAL FOR CONTAINMENT AND CLEAN UP :

Collect damaged aerosols and use absorbent and/or inert material, then place in suitable container.

7. HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING : Additional hazards when processed: Handle empty containers with care because residual vapors are flammable.

Precautions for safe handling: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when you are leaving work. Provide good ventilation in process area to prevent formation of vapor. No smoking. Use only non-sparking tools. Use outdoors or in a well ventilated area. Avoid breathing fume, vapors.

Hygiene measures: Wash Skin thoroughly after handling.

CONDITIONS FOR SAFE STORAGE, INCLUDING INCOMPATIBILITIES : Storage conditions: Store in a dry, cool and well-ventilated place away from: Heat sources. Direct sunlight.

Incompatible products: Strong bases. Strong acids.

Incompatible materials: Source of ignition. Direct sunlight. Heat Sources.

8. EXPOSURE CONTROLS\PERSONAL PROTECTION

Methyl Ethyl Ketone(78-93-3)		
USA ACGIH	ACGIH STEL (ppm)	300 ppm
USA ACGIH	ACGIH TWA (ppm)	200 ppm
USA OSHA	OSHA PEL (STEL) (ppm)	100 ppm
USA OSHA	OSHA PEL TWA (mg/m3)	410 mg/m3
n-Butyl Acetate(123-86-4)		
USA ACGIH	ACGIH STEL	200 ppm
USA ACGIH	ACGIH TWA	150 ppm
USA OSHA	OSHA PEL (Table Z-1)	150 ppm, 710 mg/m3

PERSONAL PROTECTIVE EQUIPMENT

RESPIRATORY PROTECTION : If TLV of the product or any component is exceeded, a NIOSH approved dust respirator is advised in absence of environmental control. OSHA Regulations also permit other NIOSH dust respirators under specified conditions. (See your Safety Equipment Supplier) Engineering or administrative controls should be implemented to reduce exposure.

HAND PROTECTION REMARKS : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

EYES PROTECTION : Eye wash bottle with pure water.
Tightly fitting safety goggles.
Where face-shield and protective suit for abnormal processing problems.

SKIN AND BODY PROTECTION : Wear impervious clothing. Choose body protection according to the amount and concentration of the dangerous substance at the work place.

WORK HYGIENIC PRACTICES: When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	:	Liquid
Color	:	Various colors depending on the pigmentation.
Odor	:	Characteristic. Sweet. Mint like.
Odor threshold	:	No data available.
Ph	:	N/A - See Technical Data Sheet
Evaporation rate	:	Slower Than Ether
Melting point	:	-94.7 C (-138.46 F)
Freezing point	:	No data available.
Boiling point	:	175.0 deg F TO 260.0 deg F
Flash point	:	24.00 deg F
Lower explosion limit	:	1.7
Upper explosion limit	:	11.0
Vapor pressure	:	185 mm Hg
Vapor density	:	Heavier than air
Relative density	:	No data available.
Density	:	7.0893
Solubility	:	No data available.
Partion coefficient: n-octanol/water	:	No data available.
Autoignition temperature	:	No data available.
Decomposition temperature	:	No data available.

10. STABILITY AND REACTIVITY

REACTIVITY : No dangerous reaction known under conditions of normal use.

CHEMICAL STABILITY : Stable under normal conditions.

CONDITIONS TO AVOID : Extremely high temperatures, poor ventilation and excessive aging.

INCOMPATIBLE MATERIALS : Avoid contact with strong oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon dioxide (CO₂), carbon monoxide (CO), oxides of nitrogen (NO_x), dense black smoke.

11. TOXICOLOGICAL INFORMATION

Methyl Ethyl Ketone(78-93-3)	
Aspiration toxicity	Product: May be harmful if swallowed and enters airways.
Carcinogenicity	Remarks: This information is not available, Carcinogenicity-Assement: Not classified as a human carcinogen.
Further information	Product Remarks: Symptoms of overexposure may be headache, diaainess, titedness, nausea and vomiting.,
Germ cell mutagenicity	Genotoxicity in vitro: Test Type: Ames test, Metabolic activation: with and without metabolic activation, Method OECD Test Guideline 471
LC50 (mouse) inhalation	320 mg/l (4 h exposure)
LC50 (rat) Oral	3737 mg/kg
LD50 (rabbit) dermal	6,480 mg/kg
Reproductive toxicity	Effects on fetal development, Species: rat female, Application Route: Inhalation, Dose: 400, 1000, 3000 ppm,
Respiratory or skin sensitisation	Test Type: Buehler Test, Species guinea pig, Method OECD Test Guideline 406, Result: Did not cause sensitization on laboratory animals.
Serious eye damage/ eye irritation	Remarks: Severe skin irritation, Species rabbit, Exposure time 24 h, Result: Irritation to eyes
Skin corrosion/irritation	Remarks: Moderate skin irritation, Species rabbit, Exposure time 24 h, Result: Mild skin irritation
STOT - repeated exposure	Product: No data available, Components: No data available.
STOT - single exposure	Product: Target Organs: Central Nervous system, Components: Exposure routes: Inhalation, Product: Target Organs: Central Nervous system
n-Butyl Acetate(123-86-4)	
Aspiration hazard	No data available.
Carcinogenicity	No data available.
Inhalation	No data available.
LD-50 Dermal - (Rabbit)	> 16ml/kg
LD-50 Oral - (Rat)	14,130 mg/kg
Mutagenicity	In vitro: No data available. In vivo: No data available.
Other adverse effects:	No data available.
Repeated dose toxicity	No data available.
Reproductive toxicity	No data available.
Respiratory or skin sensitization	Skin Sensitization:, (Guinea Pig) - non-sensitizing.
Serious eye damage/eye irritation	(Rabbit, 24 h): none
Skin corrosion/irritation	(Rabbit, 24 h): none
Specific target organ toxicity - repeated exposure	No data available.
Specific target organ toxicity - single exposure	Narcotic effect.

12. ECOLOGICAL INFORMATION

Methyl Ethyl Ketone(78-93-3)	
Bioaccumulative potential	Partition coefficient: n-octanol/water: log Pow: 2.49
EC50 (Algae)	2029 mg/l (48 h; Pseudokirchneriella subcapitata (Green Algae))
EC50 (Daphnia)	308 mg/l (48 h; Daphnia magna (Water flea))
LC50 (fish)	2993 mg/l (96 h; Pimephales promelas (Fathead minnow))

Mobility in soil	No data available
Other adverse effects	No data available
Persistence and degradability	Biodegradability: Concentration: 2mg/l; Result: Readily biodegradation: 98%; Exposure 28 d;
Product	Regulation: 40CFR Protection of Environment, Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class 1 Substances:
n-Butyl Acetate(123-86-4)	
Bioaccumulative potential	No data available.
Chronic Toxicity	Fish: No data available. Aquatic invertebrates: No data available. Toxicity to Aquatic Plants: No data available.
LC-50 (Fathead Minnow) Acute Toxicity	18 mg/l, (96 h)
LC-50 (Water Flea) Aquatic invertebrates	44 mg/l , (48 h)
Mobility in soil	Known or predicted distribution to environmental compartments: No data available.
Other adverse effects	No data available.
Persistence and degradability	83 % (28 d), Biological Oxygen Demand:BOD-5: 730 mg/g, Chemical Oxygen Demand:1,010 mg/g, BOD/COD ratio:72 %.
Results of PBT and vPvB assessment	No data available.

13. DISPOSAL CONSIDERATIONS

WASTE TREATMENT METHODS

GENERAL INFORMATION : No data available.

DISPOSAL METHOD: Dispose of waste and residues in accordance with Local, State, and Federal Regulations. Mix with compatible chemical which is less flammable and incenerate. Since emptied containers retain product residue, follow label warnings even after container is emptied. Residual vapors may explode on ignition; do not cut, drill, grind or weld or near this container.

14. TRANSPORT INFORMATION

***CHECK WITH YOUR CARRIER FOR ADDITIONAL RESTRICTIONS THAT MAY APPLY.**

USDOT GROUND

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME (DOT) : Paint Related Material

HAZARDS CLASS : 3

UN/NA NUMBER : UN1263

PACKING GROUP : PG II

EMERGENCY RESPONSE GUIDE (ERG) : 128

IATA (AIR)

DOT (INTERNATIONAL AIR TRANSPORTATION ASSOCIATION)

PROPER SHIPPING NAME : Paint, flammable liquid

HAZARDS CLASS : 3

UN/NA NUMBER : UN1263

PACKING GROUP : PG II

EMERGENCY RESPONSE GUIDE (ERG) : 128

IMDG (OCEAN)

PROPER SHIPPING NAME : Paint, flammable liquid

HAZARDS CLASS : 3

UN/NA NUMBER : UN1263

PACKING GROUP : PG II

EMERGENCY RESPONSE GUIDE (ERG) : 128

MARINE POLLUTANT : No

SPECIAL PRECAUTIONS : P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking. P235 Keep cool.

15. REGULATORY INFORMATION

US FEDERAL REGULATIONS

All ingredients in Section #3 are TSCA (Toxic Substance Control Act) listed.

OSHA HAZARDS : Flammable liquid, Moderate skin irritant, Moderate eye irritant, Carcinogen.

EPCRA - Emergency

CERCLA REPORTABLE QUANTITY

This product contains:	Chemical CAS#
n-Butyl Acetate	123-86-4
Methyl Ethyl Ketone	78-93-3

SARA 304 Extremely Hazardous Substances Reportable Quantity : This material does not contain any components with a section 304 EHS RQ.

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

SARA 311/312 Hazards : Fire Hazard, Acute Health Hazard, Chronic Health Hazard

SARA 313 :

This product contains:	Chemical CAS#
n-Butyl Acetate	123-86-4
Methyl Ethyl Ketone	78-93-3

CLEAN AIR ACT :

INTERNATIONAL REGULATIONS

CLASSIFICATION ACCORDING TO REGULATION (EC) No. 1272/2008 (CLP) :

Flam. Liq. Cat. 2; H226
Acute Tox. Inhalation, Cat. 4; H332
STOT SE, Inhalation, Cat. 3; H335
Skin Sens. Cat. 1; H317

NATIONAL REGULATIONS

Indicates a chemical listed by IARC as a possible carcinogen.

STATE REGULATIONS

CALIFORNIA PROPOSITION 65

*This product contains (a) chemical (s) known to the State of California to cause cancer.

#This product contains (a) chemical (s) known to the State of California to be carcinogenic.

+This product contains (a) chemical (s) known to the State of California to cause birth defects or other reproductive harm.

Massachusetts Right to Know

This product contains	Chemical CAS#
n-Butyl Acetate	123-86-4
Methyl Ethyl Ketone	78-93-3

Pennsylvania Right to Know

This product contains	Chemical CAS#
n-Butyl Acetate	123-86-4
Methyl Ethyl Ketone	78-93-3

New Jersey Right to Know

This product contains	Chemical CAS#
n-Butyl Acetate	123-86-4

Methyl Ethyl Ketone	78-93-3
---------------------	---------

16. OTHER INFORMATION

Other Product Information


% Volatile by Volume: 100.00	% Volatile by Weight: 100.00
% Solids by volume: 0.00	% Solids by Weight: 0.00
% Exempt by Volume: 0.00	% Exempt by Weight: 0.00

VOC CONTENT: Excluding Exempt VOC: 850
Including Exempt VOC: 850

HMIS RATING

Health :	2*
Flammability :	3
Reactivity :	0
Personal Protection :	H

NFPA CODES



MANUFACTURER DISCLAIMER : The information contained in this Safety Data Sheet is considered to be true and accurate. Cardinal Industrial Finishes makes no warranties, expressed or implied, as to the accuracy and adequacy of this information. This data is offered solely for the user's consideration, investigation and verification.