

# C241-GR487 PMS 427C GRAY

### 1. PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** C241-GR487 PMS 427C GRAY **PRODUCT USE: Industrial Powder Coating** 

**MANUFACTURER** 

Cardinal Paint and Powder 1329 Potrero Ave S. El Monte, CA, 91733

626 444-9274

24 HR. EMERGENCY TELEPHONE NUMBER

CHEMTREC (US Transportation): (800)424-9300 **CHEMTREC (International Transportation)**: (202)483-7616

WEB: WWW.CARDINALPAINT.COM

### 2. HAZARDS IDENTIFICATION

#### **PICTOGRAMS:**



**SIGNAL WORD: WARNING** 

### **HAZARD STATEMENTS:**

H351 Suspected of causing cancer.

H372 Causes damage to organs through prolonged or repeated exposure.

H317 May cause an allergic skin reaction.

# PRECAUTIONARY STATEMENTS:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe dust.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	Weight %	CAS Number
Titanium Dioxide	15% - 20%	13463-67-7
Hydrated magnesium silicate	1% - 5%	14807-96-6
Aluminum Oxide	<1%	1344-28-1
Crystalline Silica	0.10% - 0.50%	14808-60-7

# 4. FIRST AID MEASURES

#### Description of first aid measures.

EYE CONTACT: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor/physician.



# **SAFETY DATA SHEET**

**ISSUED:** 8/23/2018 **REFERENCE:** GR487-C241

**SKIN CONTACT:** Remove affected clothing and wash all exposed area with mild soap and water, followed by warm water rinse. Wash with plenty of soap and water. If skin irritation or rash occurs: Wash with plenty of soap and water. Get medical advice/attention. Wash contaminated clothing before reuse. Brush off loose particles from skin. Immerse in cool water/wrap in wet bandages.

**INGESTION:** Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. Call a Poison Center or doctor/physician of you feel unwell.

**INHALATION:** Allow victim to breathe fresh air. Allow victim to rest. Remove to fresh air and keep at rest in a position comfortable to breath. Call a Poison Center or doctor/physician if you feel unwell.

**Most important symptoms and effect, both acute and delayed :** Symptoms/Injuries: May cause genetic defects. Causes damage to organs. - After Inhalation: Danger of serious damage to health by prolonged exposure through inhalation. Harmful if inhaled. May cause an allergic skin reaction. May cause cancer by inhalation. - After Eye Contact: Causes serious eye damage. - After Ingestion: Swallowing a small quantity of this material may result in serious health hazard. Indication of any immediate medical attention and special treatment needed: No additional information available.

#### 5. FIRE FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA: Foam, alcohol foam, dry chemical, carbon dioxide, water fog or sand.

UNSUITABLE EXTINGUISHING MEDIA: Do not use heavy water stream.

**FIRE FIGHTING PROCEDURE:** Firefighting instructions: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering the environment.

Protection during firefighting: Firefighters should wear full protective gear. Do not enter fire area without proper protective equipment, including self-contained breathing apparatus with full face piece operated in pressure demand or other positive pressure modes.

UNUSUAL FIRE AND EXPLOSION HAZARD: This product is stable at normal handling and storage conditions.

# **6. ACCIDENTAL RELEASE MEASURES**

**PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES :** General measures: Remove ignition sources. Use special care to avoid static electric charges. No smoking.

FOR NON-EMERGENCY PERSONNEL: For non-Emergency procedures: Evacuate unnecessary personnel.

**FOR EMERGENCY RESPONDERS :** Protective equipment : Equip cleanup crew with proper protection. - Emergency procedures : Ventilate area.

**ENVIRONMENTAL PRECAUTIONS:** Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public water. Avoid release to the environment.

**METHODS AND MATERIAL FOR CONTAINMENT AND CLEAN UP:** On land, sweep or shovel into suitable containers,. Minimize generation of dust.

#### 7. HANDLING AND STORAGE

**PRECAUTIONS FOR SAFE HANDLING:** Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when you are leaving work. Provide good ventilation in process area. Use only in well ventilated areas. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Eliminate all ignition sources if safe to do so. Avoid breathing dust, fumes and/or vapors.

Hygiene measures: Wash Skin thoroughly after handling.

**CONDITIONS FOR SAFE STORAGE, INCLUDING INCOMPATIBILITIES:** Avoid heat sources and direct sunlight. Store in a dry place. Protect from moisture. Keep container closed when not in use. Keep only in the original container in a cool well ventilated place away from heat, ignition sources and direct sunlight.

Incompatible products: Strong bases. Strong acids.

Incompatible materials: Source of ignition. Direct sunlight.



# 8. EXPOSURE CONTROLS\PERSONAL PROTECTION

USA ACGIH USA ACGIH (TLV) TWA 1 mg/m3  Morphous Pyrogenic Silica(112945-52-5) USA OSHA USA OSHA USA OSHA USA OSHA USA OSHA TWA (CEL Table Z-3) USA OSHA USA OSHA USA OSHA USA OSHA TWA (Table Z-1) USA OSHA USA OSHA USA OSHA TWA (Table Z-1) USA OSHA USA OSHA TWA (Table Z-1) USA OSHA USA OSHA USA OSHA TWA (Table Z-1) USA NIOSH USA OSHA USA OSHA USA OSHA TWA (Table Z-1) USA NIOSH USA NIOSH USA OSHA USA OSHA TWA (Table Z-1) USA NIOSH USA OSHA USA OSHA TWA (Table Z-1) USA NIOSH USA NIOSH TWA (Table Z-1) USA NIOSH USA NIOSH TWA (Table Z-1) USA NIOSH TWA (Table Z-1) USA NIOSH USA NIOSH TWA (Table Z-1) USA NIOSH TWA (Table Z-2) USA NIOSH TWA (Time Weighted Average) USA NIOSH REL (Recommended Exposure Limit) USA CRICK TWA (Time Weighted Average) USA NIOSH REL (Recommended Exposure Limit) USA NIOSH REL (Recommended Exposure Limit) USA CRICK TWA (Time Weighted Average) USA NIOSH REL (Recommended Exposure Limit) USA CRICK TWA (Time Weighted Average) USA NIOSH REL (Recommended Exposure Limit) USA (Time Weighted Average) USA NIOSH REL (Recommended Exposure Limit) USA (Time Weighted Average) USA RESpirable Fraction) 8 hours USA NIOSH REL (Recommended Exposure Limit) USA (Time Weighted Average) USA RESpirable Fraction) 8 hours USA NIOSH REL (Recommende Exposure Limit) USA (Time Weighted Average) USA RESpirable Fraction) 8 hours USA NIOSH REL (Recommende Exposure Limit) USA (Time Weighted Average) USA RESpirable Fraction) 8 hours USA RESPIRATE USA NIOSH REL (Recommende Exposure Limit) USA (Time Weighted Average) USA REPL (Permissib	Aluminum Oxide(1344-28-1)					
USA ACGIH Amorphous Pyrogenic Silica(112945-52-5) USA OSHA USA NIOSH USA NIOSH USA OSHA TWA (REL) SA MICH USA OSHA TWA (REL) USA OSHA USA OSHA USA OSHA USA OSHA USA OSHA TWA (Table Z-1) USA OSHA USA OSHA USA OSHA USA OSHA USA OSHA USA OSHA TWA (Table Z-1) USA OSHA USA OSHA USA OSHA USA OSHA USA OSHA USA OSHA TWA (Table Z-1) USA NIOSH USA NIOSH USA OSHA USA OSHA OSHA TWA (Table Z-1) USA NIOSH USA OSHA USA OSHA OSHA TWA (Table Z-1) USA NIOSH USA OSHA OSHA TWA (Table Z-1) USA NIOSH USA OSHA TWA (Table Z-1) USA OSHA USA OSHA TWA (Table Z-1) USA OSHA TWA (Table Z-1) USA OSHA USA OSHA TWA (Table Z-1) USA OSHA TWA (Table Z-1) USA OSHA TWA (Table Z-1) USA OSHA USA OSHA TWA (Table Z-1) USA OSHA TWA (Table Z-1) USA OSHA USA OSHA USA OSHA TWA (Table Z-1) USA OSHA TWA (Table Z-1) USA OSHA TWA (Table Z-1) USA OSHA		(OEL) Table Z-1, TWA	15 mg/m3			
Morphous Pyrogenic Silica(112945-52-5)   USA OSHA   USA OSHA TWA (OEL Table Z-3)   80 mg/m3 3/%SiO2     USA NIOSH   USA NIOSH TWA (REL)   6 mg/m3     Morphous Silica(112926-00-8)     USA OSHA   USA OSHA TWA (Table Z-1)   6 mg/m3     USA OSHA   USA OSHA TWA (Table Z-1)   6 mg/m3     USA OSHA   USA OSHA TWA (Table Z-3)   20 Million particals per cubic foot.     USA NIOSH   USA NIOSH TWA (REL)   6 mg/m3     USA OSHA   USA NIOSH TWA (REL)   6 mg/m3     USA OSHA   USA NIOSH TWA (REL)   6 mg/m3     Carbon Black(1333-86-4)     ACGIH TLV (Threshold Limit Value)   TWA (Time Weighted Average)   3 mg/m3 8 hours     OSHA PEL (Recommended Exposure Limit)   TWA (Time Weighted Average)   3.5 mg/m3 8 hours     NIOSH REL (Recommended Exposure Limit)   TWA (Time Weighted Average)   0.1mg of PAHs/cm3 10 hours     Limit	USA ACGIH		1 mg/m3			
USA NIOSH USA NIOSH USA NIOSH USA NIOSH USA NIOSH TWA (REL) 0 6 mg/m3  WSA OSHA WSA OSHA WSA OSHA TWA (Table Z-1) USA OSHA USA OSHA TWA (Table Z-1) USA NIOSH USA OSHA TWA (Table Z-1) USA NIOSH USA NIOSH TWA (REL) USA NIOSH TWA (Table Z-1) USA NIOSH TWA (Threshold Limit Value) OSHA PEL (Permissible Exposure Limit) NIOSH REL (Recommended Exposure Limit ) NIOSH REL (Recommended Exposure Lim	Amorphous Pyrogenic Silica(112945-52-	5)				
Amorphous Silica(112926-00-8) USA OSHA USA OSHA TWA (Table Z-1) 6 mg/m3 USA OSHA USA OSHA TWA (Table Z-1) 20 Million particals per cubic foot. USA NIOSH USA NIOSH USA NIOSH WA (Table Z-3) 20 Million particals per cubic foot. USA NIOSH USA NIOSH WA (Table Z-3) 20 Million particals per cubic foot. USA NIOSH USA NIOSH TWA (Table Z-3) 20 Million particals per cubic foot. USA NIOSH TWA (Time Weighted Average) 3 mg/m3 8 hours  OSHA PEL (Permissible Exposure Limit) TWA (Time Weighted Average) 3.5 mg/m3 8 hours  NIOSH REL (Recommended Exposure Limit (Time Weighted Average) 3.5 mg/m3 8 hours  NIOSH REL (Recommended Exposure Limit (Time Weighted Average) 3.5 mg/m3 8 hours  NIOSH REL (Recommended Exposure Limit (Time Weighted Average) 0.1 mg of PAHs/cm3 10 hours  NIOSH REL (Recommended Exposure Limit (Time Weighted Average) 1.0 mg/m3 8 hours  NIOSH REL (Recommended Exposure Limit (Time Weighted Average) 1.0 mg/m3 8 hours  NIOSH REL (Recommended Exposure Limit (Time Weighted Average) 1.5 mg/m3 8 hours  NIOSH REL (Recommended Exposure Limit (Time Weighted Average) 1.5 mg/m3 8 hours  NIOSH REL (Recommended Exposure Limit (Time Weighted Average) 1.5 mg/m3 (Respirable Fraction) 10 hours  NIOSH REL (Recommended Exposure Limit (Time Weighted Average) 1.5 mg/m3 (Respirable Fraction) 10 hours  NIOSH REL (Recommended Exposure Limit (Time Weighted Average) 1.5 mg/m3 (Respirable Fraction) 10 hours  NIOSH REL (Rermissible Exposure Limit (Time Weighted Average) 1.5 mg/m3 (Respirable Fraction) 10 hours  NIOSH REL (Recommende Exposure Limit (Time Weighted Average) 1.5 mg/m3 (Respirable Fraction) 8 hours  NIOSH REL (Recommende Exposure Limit (Time Weighted Average) 1.5 mg/m3 (Respirable Fraction) 8 hours  NIOSH REL (Recommende Exposure Limit (Time Weighted Average) 1.5 mg/m3 (Respirable Fraction) 8 hours  NIOSH REL (Recommende Exposure Limit (Time Weighted Average) 1.5 mg/m3 (Respirable Fraction) 8 hours  NIOSH REL (Recommende Exposure Limit (Time Weighted Average) 1.5 mg/m3 (Respirable Fraction) 8 hours			80 mg/m3 3/%SiO2			
USA OSHA USA OSHA TWA (Table Z-1) USA OSHA TWA (Table Z-3) USA NIOSH USA NIOSH USA NIOSH TWA (REL) Carbon Black(1333-86-4)  ACGIH TLV (Threshold Limit Value) NIOSH REL (Recommended Exposure Limit) TWA (Time Weighted Average) USA NIOSH REL (Recommended Exposure Limit) TWA (Time Weighted Average) USA NIOSH REL (Recommended Exposure Limit) NIOSH REL (Recommended Exposure Limit) TWA (Time Weighted Average) USA SBlica(14808-60-7) ACGIH TLV (Threshold Limit Value) TWA (Time Weighted Average) USA SBlica(14808-60-7) ACGIH TLV (Threshold Limit Value) TWA (Time Weighted Average) USA SBlica (14808-60-7) TWA (Time Weighted Average) USA SBlica (14808-60-7) ACGIH TLV (Threshold Limit Value) TWA (Time Weighted Average) USA SBlica (14808-60-7) TWA (Time Weighted Average) USA SBlica (14808-60-7) TWA (Time Weighted Average) USA SBlica (14808-60-7) TWA (Time Weighted Average) USA SBLICA (Threshold Limit Value) TWA (Time Weighted Average) USA SBLICA (Threshold Limit Value) TWA (Time Weighted Average) USA SBLICA (Threshold Limit Value) TWA (Time Weighted Average) USA SBLICA (Threshold Limit Value) TWA (Time Weighted Average) USA SBLICA (Threshold Limit Value) TWA (Time Weighted Average) USA SBLICA (Threshold Limit Value) USA SBLICA (Threshold Limit Value) TWA (Time Weighted Average) USA SBLICA (Threshold Limit Value) USA SBLICA (Threshold Limit	USA NIOSH					
USA OSHA USA NIOSH TWA (REL)  6 mg/m3  Carbon Black(1333-86-4)  ACGIH TLV (Threshold Limit Value) OSHA PEL (Permissible Exposure Limit) NIOSH REL (Recommended Exposure Limi	Amorphous Silica(112926-00-8)					
USA NIOSH USA NIOSH TWA (REL) 6 mg/m3  Carbon Black(1333-86-4)  ACGIH TLV (Threshold Limit Value) TWA (Time Weighted Average) 3 mg/m3 8 hours  OSHA PEL (Permissible Exposure Limit) TWA (Time Weighted Average) 3.5 mg/m3 8 hours  NIOSH REL (Recommended Exposure Limit) TWA (Time Weighted Average) 3.5 mg/m3 8 hours  NIOSH REL (Recommended Exposure Limit) TWA (Time Weighted Average) 0.1mg of PAHs/cm3 10 hours  NIOSH REL (Recommended Exposure Limit ) TWA (Time Weighted Average) 0.025 mg/m3 8 hours  NIOSH REL (Recommended Exposure Limit Value) TWA (Time Weighted Average) 0.025 mg/m3 8 hours  NIOSH REL (Recommended Exposure Limit) TWA (Time Weighted Average) 1.0 mg/m3 8 hours  NIOSH REL (Recommended Exposure Limit) TWA (Time Weighted Average) 15 mg/m3 8 hours  NIOSH REL (Recommended Exposure Limit) TWA (Time Weighted Average) 2 mg/m3 (Respirable Fraction) 8 hours  NIOSH REL (Recommended Exposure Limit) TWA (Time Weighted Average) 2 mg/m3 (Respirable Fraction) 10 hours  NIOSH REL (Recommended Exposure Limit) TWA (Time Weighted Average) 15 mg/m3 (Respirable Fraction) 10 hours  NIOSH REL (Recommended Exposure Limit) TWA (Time Weighted Average) 15 mg/m3 (Total Dust) 8 hours  NIOSH REL (Recommended Exposure Limit) TWA (Time Weighted Average) 5 mg/m3 (Respirable Fraction) 8 hours  NIOSH REL (Recommende Exposure Limit) TWA (Time Weighted Average) 5 mg/m3 (Total Dust) 8 hours  NIOSH REL (Recommende Exposure Limit) TWA (Time Weighted Average) 5 mg/m3 (Respirable Fraction) 8 hours  NIOSH REL (Recommende Exposure Limit) TWA (Time Weighted Average) 5 mg/m3 (Respirable Fraction) 8 hours  NIOSH REL (Recommende Exposure Limit) TWA (Time Weighted Average) 5 mg/m3 (Respirable Fraction) 8 hours  NIOSH REL (Recommende Exposure Limit) TWA (Time Weighted Average) 5 mg/m3 (Respirable Fraction) 8 hours	USA OSHA	USA OSHA TWA (Table Z-1)	6 mg/m3			
Carbon Black(1333-86-4) ACGIH TLV (Threshold Limit Value) OSHA PEL (Permissible Exposure Limit) NIOSH REL (Recommended Exposure Limit) NIOSH REL (Recommended Exposure Limit) TWA (Time Weighted Average) NIOSH REL (Recommended Exposure Limit) NIOSH REL (Recommended Exposure Limit) TWA (Time Weighted Average) NIOSH REL (Recommended Exposure Limit)  Crystalline Silica(14808-60-7) ACGIH TLV (Threshold Limit Value) NIOSH REL (Recommended Exposure Limit) NIOSH REL (Recommended Exposure Limit) TWA (Time Weighted Average) NIOSH REL (Recommended Exposure Limit) TWA (Time Weighted Average) NIOSH REL (Recommended Exposure Limit)  NIOSH REL (Recommended Exposure Limit) NIOSH REL (Recommended Exposure Limit) NIOSH REL (Recommended Exposure Limit) NIOSH REL (Recommended Exposure Limit) NIOSH REL (Recommended Exposure Limit) NIOSH REL (Recommended Exposure Limit) NIOSH REL (Recommended Exposure Limit) NIOSH REL (Recommended Exposure Limit) NIOSH REL (Recommended Exposure Limit) NIOSH REL (Recommended Exposure Limit) TWA (Time Weighted Average) Not Applicable Shapel (Permissible Exposure Limit) TWA (Time Weighted Average) Not Applicable Shapel (Permissible Exposure Limit) TWA (Time Weighted Average)  Not Applicable Shapel (Respirable Fraction) 8 hours  Not Applicable Shapel (Recommende Exposure Limit) NIOSH REL (Recommende Exposure TWA (Time Weighted Average) Shapel (Respirable Fraction) 8 hours  NIOSH REL (Recommende Exposure TWA (Time Weighted Average) Shapel (Respirable Fraction) 8 hours  NIOSH REL (Recommende Exposure TWA (Time Weighted Average) Shapel (Respirable Fraction) 8 hours  NIOSH REL (Recommende Exposure TWA (Time Weighted Average) Shapel (Respirable Fraction) 8 hours	USA OSHA	USA OSHA TWA (Tabla Z-3)	20 Million particals per cubic foot.			
ACGIH TLV (Threshold Limit Value) TWA (Time Weighted Average) 3 mg/m3 8 hours OSHA PEL (Permissible Exposure Limit) TWA (Time Weighted Average) 3.5 mg/m3 8 hours NIOSH REL (Recommended Exposure Limit) TWA (Time Weighted Average) 3.5 mg/m3 8 hours NIOSH REL (Recommended Exposure Limit) TWA (Time Weighted Average) 0.1mg of PAHs/cm3 10 hours Limit) Crystalline Silica(14808-60-7) ACGIH TLV (Threshold Limit Value) TWA (Time Weighted Average) 0.025 mg/m3 8 hours Diethanolamine(111-42-2) ACGIH TLV (Threshold Limit Value) TWA (Time Weighted Average) 1.0 mg/m3 8 hours NIOSH REL (Recommended Exposure Limit) TWA (Time Weighted Average) 15 mg/m3 8 hours NIOSH REL (Recommended Exposure Limit) TWA (Time Weighted Average) 3 ppm 8 hours NIOSH REL (Recommended Exposure Limit) TWA (Time Weighted Average) 2 mg/m3 (Respirable Fraction) 8 hours NIOSH REL(Recommended Exposure Limit) TWA (Time Weighted Average) 2 mg/m3 (Respirable Fraction) 10 hours  NIOSH REL(Recommended Exposure Limit) TWA (Time Weighted Average) 15 mg/m3 (Respirable Fraction) 10 hours  NIOSH REL(Recommended Exposure Limit) TWA (Time Weighted Average) 15 mg/m3 (Total Dust) 8 hours  NIOSH REL (Permissible Exposure Limit) TWA (Time Weighted Average) 5 mg/m3 (Respirable Fraction) 8 hours  NIOSH REL (Recommende Exposure Limit) TWA (Time Weighted Average) 5 mg/m3 (Respirable Fraction) 8 hours  NIOSH REL (Recommende Exposure Limit) TWA (Time Weighted Average) 5 mg/m3 (Respirable Fraction) 8 hours  NIOSH REL (Recommende Exposure Limit) TWA (Time Weighted Average) 5 mg/m3 (Respirable Fraction) 8 hours  NIOSH REL (Recommende Exposure Limit) TWA (Time Weighted Average) 5 mg/m3 (Respirable Fraction) 8 hours  NIOSH REL (Recommende Exposure Limit) TWA (Time Weighted Average) 5 mg/m3 (Respirable Fraction) 8 hours  NIOSH REL (Recommende Exposure Limit) TWA (Time Weighted Average) 5 mg/m3 (Respirable Fraction) 8 hours	USA NIOSH	USA NIOSH TWA (REL)	6 mg/m3			
ACGIH TLV (Threshold Limit Value) TWA (Time Weighted Average) 3 mg/m3 8 hours OSHA PEL (Permissible Exposure Limit) TWA (Time Weighted Average) 3.5 mg/m3 8 hours NIOSH REL (Recommended Exposure Limit) TWA (Time Weighted Average) 3.5 mg/m3 8 hours NIOSH REL (Recommended Exposure Limit) TWA (Time Weighted Average) 0.1mg of PAHs/cm3 10 hours Limit) Crystalline Silica(14808-60-7) ACGIH TLV (Threshold Limit Value) TWA (Time Weighted Average) 0.025 mg/m3 8 hours Diethanolamine(111-42-2) ACGIH TLV (Threshold Limit Value) TWA (Time Weighted Average) 1.0 mg/m3 8 hours NIOSH REL (Recommended Exposure Limit) TWA (Time Weighted Average) 15 mg/m3 8 hours NIOSH REL (Recommended Exposure Limit) TWA (Time Weighted Average) 3 ppm 8 hours NIOSH REL (Recommended Exposure Limit) TWA (Time Weighted Average) 2 mg/m3 (Respirable Fraction) 8 hours NIOSH REL(Recommended Exposure Limit) TWA (Time Weighted Average) 2 mg/m3 (Respirable Fraction) 10 hours  NIOSH REL(Recommended Exposure Limit) TWA (Time Weighted Average) 15 mg/m3 (Respirable Fraction) 10 hours  NIOSH REL(Recommended Exposure Limit) TWA (Time Weighted Average) 15 mg/m3 (Total Dust) 8 hours  NIOSH REL (Permissible Exposure Limit) TWA (Time Weighted Average) 5 mg/m3 (Respirable Fraction) 8 hours  NIOSH REL (Recommende Exposure Limit) TWA (Time Weighted Average) 5 mg/m3 (Respirable Fraction) 8 hours  NIOSH REL (Recommende Exposure Limit) TWA (Time Weighted Average) 5 mg/m3 (Respirable Fraction) 8 hours  NIOSH REL (Recommende Exposure Limit) TWA (Time Weighted Average) 5 mg/m3 (Respirable Fraction) 8 hours  NIOSH REL (Recommende Exposure Limit) TWA (Time Weighted Average) 5 mg/m3 (Respirable Fraction) 8 hours  NIOSH REL (Recommende Exposure Limit) TWA (Time Weighted Average) 5 mg/m3 (Respirable Fraction) 8 hours  NIOSH REL (Recommende Exposure Limit) TWA (Time Weighted Average) 5 mg/m3 (Respirable Fraction) 8 hours	Carbon Black(1333-86-4)					
OSHA PEL (Permissible Exposure Limit)  NIOSH REL (Recommended Exposure Limit)  ACGIH TLV (Threshold Limit Value)  Diethanolamine(111-42-2)  ACGIH TLV (Threshold Limit Value)  NIOSH REL (Recommended Exposure Limit)  Not Applicable  Not Applicable  OSHA PEL (Permissible Exposure Limit)  OSHA PEL (Permissible Exposure Limit)  NOSH REL (Recommende Exposure Limit)  NIOSH REL (Recommende Exposure Limit)  NIOSH REL (Recommende Exposure Limit)  TWA (Time Weighted Average)  Not Applicable  S mg/m3 (Respirable Fraction) 8 hours  Not Applicable  S mg/m3 (Respirable Fraction) 8 hours  NIOSH REL (Recommende Exposure Limit)  TWA (Time Weighted Average)  S mg/m3 (Respirable Fraction) 8 hours  NIOSH REL (Recommende Exposure Limit)  NIOSH REL (Recommende Exposure Limit)  TWA (Time Weighted Average)  TWA (Time Weighted Average)  S mg/m3 (Respirable Fraction) 8 hours  NIOSH REL (Recommende Exposure Limit)  TWA (Time Weighted Average)  TWA (Time Weighted Average)  S mg/m3 (Respirable Fraction) 8 hours  NIOSH REL (Recommende Exposure Limit)  TWA (Time Weighted Average)		TWA (Time Weighted Average)	3 mg/m3 8 hours			
NIOSH REL (Recommended Exposure Limit)  NIOSH REL (Recommended Exposure Limit)  Crystalline Silica(14808-60-7)  ACGIH TLV (Threshold Limit Value)  NIOSH REL (Recommended Exposure Limit)  TWA (Time Weighted Average)  ACGIH TLV (Threshold Limit Value)  TWA (Time Weighted Average)  ACGIH TLV (Threshold Limit Value)  NIOSH REL (Recommended Exposure Limit)  Not Applicable  OSHA PEL (Permissible Exposure Limit)  Not Applicable  OSHA PEL (Permissible Exposure Limit)  NIOSH REL (Recommended Exposure Limit)  NIOSH REL (Recommended Exposure Limit)  TWA (Time Weighted Average)  S mg/m3 (Respirable Fraction) 10 hours  15 mg/m3 (Total Dust) 8 hours  15 mg/m3 (Respirable Fraction) 8 hours  NIOSH REL (Recommende Exposure Limit)  TWA (Time Weighted Average)  15 mg/m3 (Total Dust) 8 hour 15 mg/m3 (Respirable Fraction) 8 hours		TWA (Time Weighted Average)	3.5 mg/m3 8 hours			
Limit)  NIOSH REL (Recommended Exposure Limit )  Crystalline Silica(14808-60-7)  ACGIH TLV (Threshold Limit Value)  Diethanolamine(111-42-2)  ACGIH TLV (Threshold Limit Value)  NIOSH REL (Recommended Exposure Limit)  NIOSH REL (Recommended Exposure Limit)  Hydrated magnesium silicate(14807-96-6)  ACGIH TLV (Threshold Limit Value)  TWA (Time Weighted Average)  TWA (Time Weighted Average)  15 mg/m3 8 hours  15 mg/m3 8 hours  15 mg/m3 (Respirable Fraction) 8 hours  NIOSH REL (Recommended Exposure Limit)  Hydrated magnesium silicate(14807-96-6)  ACGIH TLV (Threshold Limit Value)  TWA (Time Weighted Average)  NIOSH REL(Recommended Exposure Limit)  TWA (Time Weighted Average)  2 mg/m3 (Respirable Fraction) 8 hours  2 mg/m3 (Respirable Fraction) 10 hours  Limestone(1317-65-3)  ACGIH  OSHA PEL (Permissible Exposure Limit)  OSHA PEL (Permissible Exposure Limit)  TWA (Time Weighted Average)  TWA (Time Weighted Average)  5 mg/m3 (Respirable Fraction) 8 hours  NIOSH REL (Recommende Exposure Limit)  TWA (Time Weighted Average)  5 mg/m3 (Respirable Fraction) 8 hours  15 mg/m3 (Total Dust) 8 hours  TWA (Time Weighted Average)  5 mg/m3 (Respirable Fraction) 8 hours  TWA (Time Weighted Average)  TWA (Time Weighted Average)  5 mg/m3 (Respirable Fraction) 8 hours  TWA (Time Weighted Average)						
Limit ) Crystalline Silica(14808-60-7) ACGIH TLV (Threshold Limit Value) NIOSH REL (Recommended Exposure Limit)  NIOSH REL (Recommended Exposure Limit)  NIOSH REL (Recommended Exposure Limit)  Hydrated magnesium silicate(14807-96-6) ACGIH TLV (Threshold Limit Value)  NIOSH REL(Recommended Exposure Limit)  TWA (Time Weighted Average)  ACGIH TLV (Threshold Limit Value)  NIOSH REL(Recommended Exposure Limit)  Limestone(1317-65-3)  ACGIH  Not Applicable  OSHA PEL (Permissible Exposure Limit)  NOTA PEL (Permissible Exposure Limit)  NOTA PEL (Permissible Exposure Limit)  TWA (Time Weighted Average)  TWA (Time Weighted Average)  SMA PEL (Recommende Exposure Limit)  TWA (Time Weighted Average)  TWA (Time Weighted Average)  SMA PEL (Recommende Exposure Limit)  TWA (Time Weighted Average)  TWA (Time Weighted Average)  SMA PEL (Recommende Exposure Limit)  TWA (Time Weighted Average)  TWA (Time Weighted Average)  SMA (Respirable Fraction) 8 hours  TWA (Time Weighted Average)  TWA (Time Weighted Average)  TWA (Time Weighted Average)  TS mg/m3 (Total Dust) 8 hours  Timit)  Titanium Dioxide(13463-67-7)			3,			
Crystalline Silica(14808-60-7) ACGIH TLV (Threshold Limit Value) Diethanolamine(111-42-2) ACGIH TLV (Threshold Limit Value) NIOSH REL (Recommended Exposure Limit) NIOSH REL (Recommended Exposure Limit) TWA (Time Weighted Average)	NIOSH REL (Recommended Exposure	TWA (Time Weighted Average)	0.1mg of PAHs/cm3 10 hours			
ACGIH TLV (Threshold Limit Value) TWA (Time Weighted Average) 0.025 mg/m3 8 hours  Diethanolamine(111-42-2)  ACGIH TLV (Threshold Limit Value) TWA (Time Weighted Average) 1.0 mg/m3 8 hours  NIOSH REL (Recommended Exposure Limit) TWA (Time Weighted Average) 15 mg/m3 8 hours  NIOSH REL (Recommended Exposure Limit) TWA (Time Weighted Average) 3 ppm 8 hours  NIOSH REL (Recommended Exposure Limit Value) TWA (Time Weighted Average) 2 mg/m3 (Respirable Fraction) 8 hours  NIOSH REL(Recommended Exposure Limit Value) TWA (Time Weighted Average) 2 mg/m3 (Respirable Fraction) 10 hours  NIOSH REL(Recommended Exposure Limit) TWA (Time Weighted Average) 15 mg/m3 (Total Dust) 8 hours  OSHA PEL (Permissible Exposure Limit) TWA (Time Weighted Average) 5 mg/m3 (Respirable Fraction) 8 hours  NIOSH REL (Recommende Exposure Limit) TWA (Time Weighted Average) 15 mg/m3 (Total Dust) 8 hours  NIOSH REL (Recommende Exposure Limit) TWA (Time Weighted Average) 5 mg/m3 (Respirable Fraction) 8 hours  NIOSH REL (Recommende Exposure TWA (Time Weighted Average) 5 mg/m3 (Respirable Fraction) 8 hours  NIOSH REL (Recommende Exposure TWA (Time Weighted Average) 5 mg/m3 (Respirable Fraction) 8 hours  Titanium Dioxide(13463-67-7)	Limit )		,			
ACGIH TLV (Threshold Limit Value) TWA (Time Weighted Average) 0.025 mg/m3 8 hours  Diethanolamine(111-42-2)  ACGIH TLV (Threshold Limit Value) TWA (Time Weighted Average) 1.0 mg/m3 8 hours  NIOSH REL (Recommended Exposure Limit) TWA (Time Weighted Average) 15 mg/m3 8 hours  NIOSH REL (Recommended Exposure Limit) TWA (Time Weighted Average) 3 ppm 8 hours  NIOSH REL (Recommended Exposure Limit Value) TWA (Time Weighted Average) 2 mg/m3 (Respirable Fraction) 8 hours  NIOSH REL(Recommended Exposure Limit Value) TWA (Time Weighted Average) 2 mg/m3 (Respirable Fraction) 10 hours  NIOSH REL(Recommended Exposure Limit) TWA (Time Weighted Average) 15 mg/m3 (Total Dust) 8 hours  OSHA PEL (Permissible Exposure Limit) TWA (Time Weighted Average) 5 mg/m3 (Respirable Fraction) 8 hours  NIOSH REL (Recommende Exposure Limit) TWA (Time Weighted Average) 15 mg/m3 (Total Dust) 8 hours  NIOSH REL (Recommende Exposure Limit) TWA (Time Weighted Average) 5 mg/m3 (Respirable Fraction) 8 hours  NIOSH REL (Recommende Exposure TWA (Time Weighted Average) 5 mg/m3 (Respirable Fraction) 8 hours  NIOSH REL (Recommende Exposure TWA (Time Weighted Average) 5 mg/m3 (Respirable Fraction) 8 hours  Titanium Dioxide(13463-67-7)	Crystalline Silica(14808-60-7)					
Diethanolamine(111-42-2)  ACGIH TLV (Threshold Limit Value)  NIOSH REL (Recommended Exposure Limit)  NIOSH REL (Recommended Exposure Limit)  Hydrated magnesium silicate(14807-96-6)  ACGIH TLV (Threshold Limit Value)  NIOSH REL (Recommended Exposure Limit)  TWA (Time Weighted Average)  TWA (Time Weighted Average)  2 mg/m3 (Respirable Fraction) 8 hours  NIOSH REL(Recommended Exposure Limit)  NIOSH REL(Recommended Exposure TWA (Time Weighted Average)  2 mg/m3 (Respirable Fraction) 10 hours  NIOSH REL(Recommended Exposure TWA (Time Weighted Average)  Limestone(1317-65-3)  ACGIH  OSHA PEL (Permissible Exposure Limit)  OSHA PEL (Permissible Exposure Limit)  Not Applicable  OSHA PEL (Recommende Exposure Limit)  TWA (Time Weighted Average)  Not Applicable  TWA (Time Weighted Average)  15 mg/m3 (Total Dust) 8 hours  NIOSH REL (Recommende Exposure  Limit)  NIOSH REL (Recommende Exposure  Limit)  TWA (Time Weighted Average)  5 mg/m3 (Respirable Fraction) 8 hours  NIOSH REL (Recommende Exposure  Limit)  TWA (Time Weighted Average)  5 mg/m3 (Respirable Fraction) 8 hours  Titanium Dioxide(13463-67-7)		TWA (Time Weighted Average)	0.025 mg/m3 8 hours			
ACGIH TLV (Threshold Limit Value)  NIOSH REL (Recommended Exposure Limit)  Hydrated magnesium silicate(14807-96-6)  ACGIH TLV (Threshold Limit Value)  NIOSH REL(Recommended Exposure Limit)  NIOSH REL(Recommended Exposure Limit)  NIOSH REL(Recommended Exposure Limit)  NIOSH REL(Recommended Exposure Limit)  OSHA PEL (Permissible Exposure Limit)  NIOSH REL (Recommended Exposure Limit)  NIOSH REL (Recommended Exposure Limit)  Not Applicable  OSHA PEL (Permissible Exposure Limit)  NIOSH REL (Recommende Exposure Limit)  Titanium Dioxide(13463-67-7)		<u> </u>				
NIOSH REL (Recommended Exposure Limit)  NIOSH REL (Recommended Exposure Limit)  Hydrated magnesium silicate(14807-96-6)  ACGIH TLV (Threshold Limit Value)  NIOSH REL(Recommended Exposure Limit)  TWA (Time Weighted Average)  ACGIH TLV (Threshold Limit Value)  TWA (Time Weighted Average)  TWA (Time Weighted Average)  2 mg/m3 (Respirable Fraction) 8 hours  NIOSH REL(Recommended Exposure Limit)  Limestone(1317-65-3)  ACGIH  OSHA PEL (Permissible Exposure Limit)  OSHA PEL (Permissible Exposure Limit)  TWA (Time Weighted Average)  TWA (Time Weighted Average)  5 mg/m3 (Total Dust) 8 hours  TWA (Time Weighted Average)  Limit)  NIOSH REL (Recommende Exposure Limit)  NIOSH REL (Recommende Exposure Limit)  TWA (Time Weighted Average)  TWA (Time Weighted Average)  5 mg/m3 (Total Dust) 8 hour  TWA (Time Weighted Average)		TWA (Time Weighted Average)	1.0 mg/m3 8 hours			
Limit)  NIOSH REL (Recommended Exposure Limit)  Hydrated magnesium silicate(14807-96-6)  ACGIH TLV (Threshold Limit Value)  NIOSH REL(Recommended Exposure TWA (Time Weighted Average)  Limit)  NIOSH REL(Recommended Exposure TWA (Time Weighted Average)  Limestone(1317-65-3)  ACGIH  OSHA PEL (Permissible Exposure Limit)  OSHA PEL (Permissible Exposure Limit)  NIOSH REL (Recommended Exposure Limit)  NIOSH REL (Recommende Exposure TWA (Time Weighted Average)  S mg/m3 (Respirable Fraction) 8 hours  15 mg/m3 (Total Dust) 8 hour Limit)  NIOSH REL (Recommende Exposure TWA (Time Weighted Average)  Titanium Dioxide(13463-67-7)	NIOSH REL (Recommended Exposure					
Limit)  Hydrated magnesium silicate(14807-96-6)  ACGIH TLV (Threshold Limit Value)  NIOSH REL(Recommended Exposure Limit)  Not Applicable  OSHA PEL (Permissible Exposure Limit)  OSHA PEL (Permissible Exposure Limit)  NIOSH REL (Recommended Exposure Limit)  TWA (Time Weighted Average)  OSHA PEL (Permissible Exposure Limit)  Not Applicable  OSHA PEL (Permissible Exposure Limit)  TWA (Time Weighted Average)  Not Applicable  5 mg/m3 (Total Dust) 8 hours  NIOSH REL (Recommende Exposure Limit)  NIOSH REL (Recommende Exposure Limit)  NIOSH REL (Recommende Exposure Limit)  TWA (Time Weighted Average)  TWA (Time Weighted Average)  5 mg/m3 (Total Dust) 8 hour  15 mg/m3 (Total Dust) 8 hour  15 mg/m3 (Respirable Fraction) 8 hours  TWA (Time Weighted Average)  TWA (Time Weighted Average)  TWA (Time Weighted Average)  TWA (Time Weighted Average)	Limit)	, , , , , , , , , , , , , , , , , , , ,				
Hydrated magnesium silicate(14807-96-6)  ACGIH TLV (Threshold Limit Value)  TWA (Time Weighted Average)  NIOSH REL(Recommended Exposure Limit)  Limestone(1317-65-3)  ACGIH  OSHA PEL (Permissible Exposure Limit)  OSHA PEL (Permissible Exposure Limit)  NIOSH REL (Recommende Exposure Limit)  NIOSH REL (Recommende Exposure Limit)  TWA (Time Weighted Average)  TWA (Time Weighted Average)  TWA (Time Weighted Average)  S mg/m3 (Respirable Fraction) 8 hours  TWA (Time Weighted Average)  TWA (Time Weighted Average)  S mg/m3 (Total Dust) 8 hours  TWA (Time Weighted Average)  Limit)  NIOSH REL (Recommende Exposure Limit)  TWA (Time Weighted Average)  S mg/m3 (Respirable Fraction) 8 hours  TWA (Time Weighted Average)  S mg/m3 (Respirable Fraction) 8 hours  TWA (Time Weighted Average)  TWA (Time Weighted Average)  S mg/m3 (Respirable Fraction) 8 hours	NIOSH REL (Recommended Exposure	TWA (Time Weighted Average)	3 ppm 8 hours			
ACGIH TLV (Threshold Limit Value)  NIOSH REL(Recommended Exposure Limit)  Limestone(1317-65-3)  ACGIH  OSHA PEL (Permissible Exposure Limit)  NIOSH REL (Permissible Exposure Limit)  NIOSH REL (Permissible Exposure Limit)  NIOSH REL (Recommende Exposure Limit)  Titanium Dioxide(13463-67-7)	Limit)					
NIOSH REL(Recommended Exposure Limit)  Limestone(1317-65-3)  ACGIH  OSHA PEL (Permissible Exposure Limit)  NIOSH REL (Permissible Exposure Limit)  NIOSH REL (Recommende Exposure Limit)  Titanium Dioxide(13463-67-7)	Hydrated magnesium silicate(14807-96-					
Limit) hours  Limestone(1317-65-3)  ACGIH Not Applicable Not Applicable  OSHA PEL (Permissible Exposure Limit) TWA (Time Weighted Average) 15 mg/m3 (Total Dust) 8 hours  OSHA PEL (Permissible Exposure Limit TWA (Time Weighted Average) 5 mg/m3 (Respirable Fraction) 8 hours  NIOSH REL (Recommende Exposure Limit) TWA (Time Weighted Average) 15 mg/m3 (Total Dust) 8 hours  NIOSH REL (Recommende Exposure Limit) TWA (Time Weighted Average) 5 mg/m3 (Respirable Fraction) 8 hours  Titanium Dioxide(13463-67-7)	ACGIH TLV (Threshold Limit Value)	TWA (Time Weighted Average)				
Limestone(1317-65-3)  ACGIH  OSHA PEL (Permissible Exposure Limit)  OSHA PEL (Permissible Exposure Limit)  OSHA PEL (Permissible Exposure Limit)  TWA (Time Weighted Average)  TWA (Time Weighted Average)  NIOSH REL (Recommende Exposure  LImit)  NIOSH REL (Recommende Exposure  LImit)  TWA (Time Weighted Average)	NIOSH REL(Recommended Exposure	TWA (Time Weighted Average)				
ACGIH  OSHA PEL (Permissible Exposure Limit)  OSHA PEL (Permissible Exposure Limit)  OSHA PEL (Permissible Exposure Limit)  TWA (Time Weighted Average)  TWA (Time Weighted Average)  NIOSH REL (Recommende Exposure  LImit)  NIOSH REL (Recommende Exposure  LImit)  TWA (Time Weighted Average)			110013			
OSHA PEL (Permissible Exposure Limit) OSHA PEL (Permissible Exposure Limit) TWA (Time Weighted Average) TWA (Time Weighted Average) Simg/m3 (Total Dust) 8 hours TWA (Time Weighted Average) NIOSH REL (Recommende Exposure LImit) TWA (Time Weighted Average) TWA (Time Weighted Average) TWA (Time Weighted Average) Simg/m3 (Total Dust) 8 hours Twa (Time Weighted Average) Twa (Time Weighted Average) Twa (Time Weighted Average) Simg/m3 (Respirable Fraction) 8 hours Titanium Dioxide(13463-67-7)		Not Applicable	Not Applicable			
OSHA PEL (Permissible Exposure Limit TWA (Time Weighted Average) 5 mg/m3 (Respirable Fraction) 8 hours  NIOSH REL (Recommende Exposure LImit) TWA (Time Weighted Average) 15 mg/m3 (Total Dust) 8 hour 15 mg/m3 (Respirable Fraction) 8 hours  TWA (Time Weighted Average) 5 mg/m3 (Respirable Fraction) 8 hours  Titanium Dioxide(13463-67-7)						
NIOSH REL (Recommende Exposure LImit)  NIOSH REL (Recommende Exposure LImit)  NIOSH REL (Recommende Exposure LImit)  Titanium Dioxide(13463-67-7)  Titanium Dioxide(13463-67-7)	OSHA PEL (Permissible Exposure Limit)					
NIOSH REL (Recommende Exposure LImit)  NIOSH REL (Recommende Exposure LImit)  Titanium Dioxide(13463-67-7)  TWA (Time Weighted Average)  TWA (Time Weighted Average)  TWA (Time Weighted Average)  5 mg/m3 (Total Dust) 8 hour  5 mg/m3 (Respirable Fraction) 8 hours	OSTATI EE (TETTINOSISTE EXPOSUTE EITITE	Titire (Time Weighted /Weilage)				
LImit)  NIOSH REL (Recommende Exposure LImit)  Titanium Dioxide(13463-67-7)  Titanium Dioxide(13463-67-7)	NIOSH REL (Recommende Exposure	TWA (Time Weighted Average)				
NIOSH REL (Recommende Exposure LImit)  Titanium Dioxide(13463-67-7)  Titanium Dioxide(13463-67-7)  Titanium Dioxide(13463-67-7)		Time (time treighted / treidge/	255, ( . 5 ca. 2 ast) 5			
LImit) hours Titanium Dioxide(13463-67-7)		TWA (Time Weighted Average)	5 mg/m3 (Respirable Fraction) 8			
Titanium Dioxide(13463-67-7)			, · · · · · · · · · · · · · · · · · · ·			
ACOIN ILV (INICONOU LINIK VAIUE)   I WA (INIE WEIGHKEU AVELAGE)   I IV ING/INO O NOUIS	ACGIH TLV (Threshold Limit Value)	TWA (Time Weighted Average)	10 mg/m3 8 hours			
OSHA PEL (Permissible Exposure Limit) TWA (Time Weighted Average) 15 mg/m3 8 hours						

### PERSONAL PROTECTIVE EQUIPMENT

**RESPIRATORY PROTECTION:** Wear approved dust mask.

**HAND PROTECTION:** Wear protective gloves.

**EYE PROTECTION:** Chemical goggles or safety glasses.

**SKIN AND BODY PROTECTION:** Wear suitable protective clothing.

WORK HYGIENIC PRACTICES: When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.



# 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	:	Solid
Melting point	:	55 - 90 deg C
Flash point	:	No data available.
Lower explosion limit	:	10 g/m <sup>3</sup>
Upper explosion limit	:	70 g/m <sup>3</sup>
Density	:	1.6305
Solubility	:	No data available.
Autoignition temperature	:	No data available.
Decomposition temperature	:	No data available.

# **10. STABILITY AND REACTIVITY**

**REACTIVITY:** This product is stable at normal handling and storage conditions.

**CHEMICAL STABILITY:** Stable under normal conditions.

**CONDITIONS TO AVOID:** Direct sunlight. Extremely high or low temperatures.

**INCOMPATIBLE MATERIALS:** Strong acids. Strong bases.

HAZARDOUS DECOMPOSITION PRODUCTS: Fume. Carbon monoxide. Carbon dioxide.

# 11. TOXICOLOGICAL INFORMATION

Aluminum Oxide(1344-28-1)	
Acute toxicity - LD50 - oral - rat	> 10,000 mg/kg
Acute toxicity - LC50 - inhalation - rat	> 2.6 mg/L / 4 h
Acute toxicity - dermal	No data available
Skin irritation - rabbit	No skin irritation
Eye irritation - rabbit	No eye irritation
Respiratory or skin sensitisation -	DId not cause sensitisation on laboratory animals
maximisation test - guinea pig	,
Germ cell mutagenicity	No data available
Carcinogenicity	This product is or contains a component that is not classifiable as to its carcinogenicty based on its IARC, ACGIH, NTP, or EPA classification
IARC	No component of this product present at levels greater than or equal to 0.1% is identified as a probable, possible or confirmed human carcinogen by IARC
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP
OSHA	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA
Reproductive toxicity	No data available
Specific target organ toxicity - single exposure	No data available
Specific target organ toxicity - repeated exposure	No data available
Aspiration hazard	No data available
Additional information	Cough, chest pain, difficulty in breathing, gastrointestinal disturbance
Addittional information	Liver irregularities based on human evidence
Amorphous Pyrogenic Silica(112945-52-5)	
Acute toxicity - Inhalation	No data available
Acute toxicity - Dermal	No data available
Skin irritation	No data available
Respiratory or skin sensation	No data available
Germ cell mutagenicity - rat - lungs	Body fluid assay
Germ cell mutagenicity - rat	Unscheduled DNA synthesis
Carcinogenicity - Rat - Inhalation	Tumorigenic: Carcinogenic by RTECS criteria. Lungs, thorax, or respiration: tumors
IARC	Not classifiable as to its carcinogenicity to human
ACGIH	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH



NTP	No component of this product present at levels greater than or equal to 0.1% is identified as as known or anticipated carcinogen
OSHA	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA
Reproductive toxicity	No data available
Specific target organ toxicity - single	No data available
exposure	The data dvallable
Specific target organ toxicity - repeated exposure	No data available
Aspiration hazard	No data available
Additional information	To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated
Additional information	Stomach irregularities based on human evidence
Amorphous Silica(112926-00-8)	
Acute toxicity	no data available
Acute toxicity: Inhalation	no data available
Acute toxicity: Immidation  Acute toxicity: Dermal	no data available
Skin irritation	no data available
Eye irritation	no data available
Respiratory or skin sensation	no data available
Germ cell mutagenicity	no data available
Carcinogenicity: IARC: Group 3:	not classifiable as to its carcinogenicity to humans
ACGIH	no component of this product present at levels greater than or equal to
	0.1% is identified as a carcinogen or potential carcinogen by ACGIH
NTP	no component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP
OSHA	no component of this product present at levels greater than or equal to
OSTIA	0.1% is identified as a carcinogen or potential carcinogen by OSHA
Deproductive toxicity	no data available
Reproductive toxicity	
Specific target organ toxicity - single	no data available
exposure	
Specific target organ toxicity - repeated exposure	no data available
Aspiration hazard	no data available
Additional information	Amorphous silica is not classified as to its carcinogenicity to humans, however, crystalline silica inhaled in the form of quartz or cristobalite from occupational sources is carcinogenic to humans (Group 1, IARC). Therefore, amorphous silica should be handled as if possessing the same hazards as the crystalline form. To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.
Additional information	Stomach - irregularities - based on human evidence
Carbon Black(1333-86-4)	
LD50 Oral - Rat	> 8,000 mg/kg, male and female, (OECD Test Guideline 401)
LD50 Inhalation - Rat	No data available
LD50 Dermal - Rabbit	> 3,000 mg/kg
Skin corrosion/irritation	No skin irritation - 24 h, (OECD Test Guideline 404)
Eye damage/irritation - Rabbit	No eye irritation, (OECD Test Guideline 404)
Respiratory/skin sensitization - Guinea pig	Did not cause sensitization on laboratory animals, (OECD Test Guideline 406)
Germ cell mutagenicity	Ames test, S. typhimurium, negative
Hamster - Ovary	Negative
DNA repair - Rat - Female	Negative
Carcinogenicity - Rat - Inhalation	Tumorigenic: Carcinogenic by RTECS criteria. Lungs, Thorax, or Respiration: Tumors. This product is or contains a component that has been reported to be possibly carcinogenic based on its IARC, ACGIH, NTP, or EPA classification. Limited evidence of carcinogenicity in animal studies.
IARC	2B - Group 2B: Possibly carcinogenic to humans (carbon black)
NTP	No component of this product present at levels greater than or equal to0.1% is identified as a known or anticipated carcinogen by NTP
OSHA	No component of this product present at levels greater than 0.1% is identified as a carcinogen or potential carcinogen by OSHA
Reproductive toxicity	No data available
Organ toxicity	Specific target organ toxicity - single exposure: No data available
Organ toxicity	Specific target organ toxicity - repeated exposure: No data available
Aspiration hazard	No data available
, sopridion nazara	no data available



Additional Information	DTFCC, FFF000000 To the best of our knowledge, the showing whysical
Additional Information	RTECS: FF5800000 To the best of our knowledge, the chemical , physical, and toxicological properties have not been throughly investigated.
Crystalline Silica(14808-60-7)	and toxicological properties have not been throughly investigated.
Acute Inhalation toxicity	no data available
Acute Dermal toxicity	no data available
Skin irritation	no data available
eye irritation	no data available
Respiratory or skin sensation	no data available
Germ cell mutagenicity	no data available
Carcinogenicity	Limited evidence of carcinogenicity in human studies
IARC	Group 1: Carcinogenic to humans (Quartz)
ACGIH	No component of this product present at levels greater than or equal to
	0.1% is identified as a carcinogen or potential carcinogen by ACGIH
NTP	Known to be human carcinogen (Quartz)
OSHA	No component of this product present at levels greater than or equal to
	0.1% is identified as a carcinogen or potential carcinogen by OSHA
Reproductive toxicity	no data available
Specific target organ toxicity - single exposure	no data available
Specific target organ toxicity - repeated exposure - inhalation	may cause damage to organs through prolonged or repeated exposure
Aspiration hazard	no data available
Additional information	Prolonged inhalation of crystalline silica may result in silicosis, a disabling pulmonary fibrosis characterized by fibrotic changes and miliary nodules in the lungs, a dry cough, shortness of breath, emphysema, decreased chest expansion, and increased susceptibility to tuberculosis. In advanced
	stage, loss of appetite, pleuric pain, and total incapacity to work.  Advanced silicosis may result in death due to cardiac failure or destruction of lung tissue. Crystalline silica is classified as group 1 "known to be carcinogenic to humans" by IARC and "sufficient evidence" of
	carcinogenicity by the NTP., The chronic health risks are associated with respirable particles of 3-4 um over protracted periods of time. Currently, there is a limited understanding of the mechanisms of quartz toxicity, including its mechanisms for lung carcinogenicity. Additional studies are needed to determine whether the cell transforming activity of quartz is
Additional information	related to its carcinogenic potential.
Additional information Diethanolamine(111-42-2)	Liver - Irregularities - based on human evidence
LD50 Oral - Rat - male and female	1,600 mg/kg (OECD Test Guideline 401)
LD50 Dermal - Rabbit	12,200 mg/kg
LD50 Intraperitoneal - Rat	120 mg/kg
LD50 Intravenous - Rat	778 mg/kg
Skin Corrosion/irritation	No data available
Serious eye damage/eye irritation	Rabbit - Risk of serious damage to eyes (OECD Test Guideline 405)
Respiratory or skin sensitization	Guinea pig - Did not cause sensitization on laboratory animals
Germ cell mutagenicity	Micronucleus test lymphocyte - Result Negative
Mutagenicity (micronucleus test) Mouse male and female	Result: Negative
Carcinogenicity - IARC	2B - Group 2B Possibly carcinogenic to humans
Carcinogenicity - NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP
Carcinogenicity - OSHA	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA
Reproductive toxicity	No data available
Specific target organ toxicity - single exposure	No data available
Specific target organ toxicity - repeated exposure	No data available
Aspiration hazard	No data available
Additional information	Repeated dose toxicity - rat - male and female - oral Lowest observed adverse effect level - 25 mg/kg RTECS: KL297500
Additional information	To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated
Additional information	Liver - Irregularities - Based on Human Evidence
Hydrated magnesium silicate(14807-96-6)	
Acute toxicity - inhalation	No data available
Acute toxicity - dermal	No data available



Ckin irritation human	Mild skin irritation 3 h
Skin irritation - human  Eye irritation	No data available
Respiratory or skin sensitisation	No ata available
Germ cell mutagenicity	No data available
Carcinogenicity - rat - inhalation	
Carcinogenicity - rat - innaiation	Equivocal tumorigenic agent by RTECS criteria. Lungs, thorax, or
IARC	respiration: Tumors Group 3: Not classifiable as to its carcinogenicity to humans
NTP	No component of this product present at levels greater than or equal to
	0.1% is identified as a known or anticipated carcinogen by NTP
OSHA	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA
Reproductive toxicity	No data available
Specific target organ toxicity - single exposure	No data available
Specific target organ toxicity - repeated exposure	No data available
Aspiration hazard	No data available
Additional information	To the best of our knowledge, the chemical, physical, and toxicological
	properties have not been thoroughly investigated
Additional information	Stomach irregularities based on human evidence
Limestone(1317-65-3)	T 750 (0.41)
Draize test, rabbit, eye	750 ug/24H severe
Draize test, rabbit, skin	500 mg/24H moderate
Oral, rat: LD50	6450 mg/kg
ACGIH, IARC, NTP, CA Prop 65	Not listed
Epidemiology	No information available
Teratogenicity	No information available
Reproductive effects	No information available
Mutagenicity	No information available
Neurotoxicity	No information available
Titanium Dioxide(13463-67-7)	
Acute toxicity - LD50 - oral - rat	> 10000 mg/kg
Acute toxicity - inhalation	No data available
Acute toxicity - LD50 - dermal - rabbit	> 10000 mg/kg
Skin irritation - human	Mild skin irritation - 3 h
Eye irritation - rabbit	No eye irritation
Respiration or skin sensitisation	Will not occur
Germ cell mutagenicity - hamster - ovary - micronucleus test	No results available
Germ cell mutagenicity - hamster - lungs	DNA inhibition
Germ cell mutagenicity - hamster - ovary -	No results available
sister chromatid exchange	
Germ cell mutagenicity - mouse - micronucleus test	No results available
IARC	No component of this product present at levels greater than or equal to 0.1% is identified as a probable, possible or confirmed human carcinogen by IARC
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen
OSHA	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA
Reproductive toxicity	No data available
Specific target organ toxicity - single	No data available
exposure	add drainable
Specific target organ toxicity - repeated exposure	No data available
Aspiration hazard	No data available
Additional information	To the best of our knowledge, the chemical, physical, and toxicological
, adiaona information	properties have not been thoroughly investigated

# 12. ECOLOGICAL INFORMATION

Aluminum Oxide(1344-28-1)	
Toxicity	No toxicity at the limit of solubility
Persisitence and degradability	The methods for determining biodegradability are not applicable to
	inorganic substances



Bioaccumulative potential	Does not bioaccumulate
Mobility in soil	No data available
PBT and vPvB	Not available/not required
Other adverse effects	No data available.
Amorphous Pyrogenic Silica(112945-52-5)	
Toxicity	No data available
Persistence and degradability	No data available
Bioaccumulative potential	No data available
Mobility in soil	No data available
PBT and vPvB	not available/not required
Amorphous Silica(112926-00-8)	Thot available/hot required
Toxicity	no data available
Persistence and degradability	no data available
Bioaccumulative potential	no data available
Mobility in soil	no data available
PBT and vPvB	not available not available/not required
Carbon Black(1333-86-4)	not available/not required
	Dania vavia (zahva fizh) > 1000 ma /l OC h
Toxicity to fish LC50	Danio rerio (zebra fish) >1000 mg/l - 96 h
EC50 Toxicity to daphnia and other aquatic invertebrates	Daphnia magna (Water flea) > 5600 mg/l - 24 h (OECD Test Guideline 202)
EC50 Toxicity to algae	Desmodesmus subspicatus (green algae > 10,000 mg/l - 72 h (OECD Test Guideline 201)
Persistence and degradability	No data available
Bioaccumulative potential	No data available
Mobility in soil	No data available
PBT and vPvB assessment	Not available/not required
Crystalline Silica(14808-60-7)	1 Not available/flot required
Toxicity	no data available
Persistence and degradability	no data available
Bioaccumulative potential	no data available
Mobility in soil	no data available
PBT and vPvB	not available not required
Diethanolamine(111-42-2)	Thot available/hot required
Toxicity to fish	LC50 - Pimephales promelas (fathead minnow) - 1,460 mg/l - 96h
Toxicity to daphnia and other aquatic	static test EC50 - Daphnia magna (Water Flea) - 30.1 mg/l - 48h
invertebrates	
Persistence and degradability	Biodegradability - aerobic - Exposure time 28d - Result: 93% Readily biodegradable ( OECD Test Guideline 301F)
Bioaccumulative potential	No data available
Mobility in Soil	No data available
Results of PBT and vPvB assessment	PBT/vPvB assessment not available as chemical safety assessment not required/not conducted
Other adverse effects	An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Harmful to aquatic life with long
Hydratod magnasium silicata (14907.00.0)	lastting effects
Hydrated magnesium silicate(14807-96-6)	No data available
Toxicity	No data available
Persistence and degradability	No data available
Bioaccumulative potential	No data available
Mobility in soil	No data available
PBT and vPvB	Not available/not required
Limestone(1317-65-3)	No data available
Ecotoxicity	No data available
Environmental	No information reported
Physical Till (12/162 67 7)	No information available
Titanium Dioxide(13463-67-7)	
Toxicity to fish - LC50 - other fish	> 1000 mg/L / 96 h
Toxicity to daphnia and other aquatic invertebrates - EC50 - Dapphnia magna	> 1000 mg/L / 48 h
(water flea) Toxicity to daphnia and other aquatic invertebrates - EC0 - Daphnia magna (water flea)	1000 mg/L / 48 h
Persistence and degradability	No data available
Bioaccumulative potential	No data available
Mobility in soil	No data available
וווסטווונץ ווו סטוו	1 110 data available



PBT and vPbV	Not available/not required
Other adverse effects	No data available

# 13. DISPOSAL CONSIDERATIONS

#### **WASTE TREATMENT METHODS**

**GENERAL INFORMATION:** No data available.

**DISPOSAL METHOD:** Dispose of in accordance with Local, State, Regional, National and International Regulations.

Ecology - waste materials: Avoid release to the environment.

# 14. TRANSPORT INFORMATION

### \*CHECK WITH YOUR CARRIER FOR ADDITIONAL RESTRICTIONS THAT MAY APPLY.

**USDOT GROUND** 

**DOT (DEPARTMENT OF TRANSPORTATION)** 

PROPER SHIPPING NAME (DOT): Not Regulated/Not Applicable

**HAZARDS CLASS:** None

UN/NA NUMBER: Not Applicable

**PACKING GROUP:** None

EMERGENCY RESPONSE GUIDE (ERG): Not Applicable

IATA (AIR)

**DOT (INTERNATIONAL AIR TRANSPORTATION ASSOCIATION)** 

PROPER SHIPPING NAME: Not Regulated/Not Applicable

**HAZARDS CLASS:** Not Applicable UN/NA NUMBER: Not Applicable **PACKING GROUP:** Not Applicable

EMERGENCY RESPONSE GUIDE (ERG): Not Applicable

IMDG (OCEAN)

PROPER SHIPPING NAME: Not Regulated, Not Applicable

**HAZARDS CLASS:** Not Applicable UN/NA NUMBER: Not Applicable PACKING GROUP: Not Applicable

EMERGENCY RESPONSE GUIDE (ERG): Not Applicable

**MARINE POLLUTANT:** No

SPECIAL PRECAUTIONS: P235 Keep cool.



# **SAFETY DATA SHEET**

**ISSUED:** 8/23/2018 **REFERENCE:** GR487-C241

### 15. REGULATORY INFORMATION

US FEDERAL REGULATIONS
All ingredients are TSCA (Toxic Substance Control Act) listed.

OSHA HAZARDS: Moderate skin irritant, Moderate eye irritant.

**EPCRA - Emergency** 

**CERCLA REPORTABLE QUANTITY** 

**SARA 304 Extremely Hazardous Substances Reportable Quantity:** This material does not contain any components with a section 304 EHS RQ.

# SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

SARA 311/312 Hazards: Acute Health Hazard, Chronic Health Hazard

This product contains:	Chemical CAS#
Titanium Dioxide	13463-67-7
Hydrated magnesium silicate	14807-96-6
Aluminum Oxide	1344-28-1
Crystalline Silica	14808-60-7

SARA 313: No SARA 313 chemicals are present

# **CLEAN AIR ACT:**

#### **INTERNATIONAL REGULATIONS**

# CLASSIFICATION ACCORDING TO REGULATION (EC) No. 1272/2008 (CLP):

Carc. 2 H351 Suspected of causing cancer

STOT RE 1 H372 Causes damage to organs through prolonged or repeated exposure

#### **NATIONAL REGULATIONS**

Th	nis product contains:	Chemical CAS#
~7	Titanium Dioxide	13463-67-7
^(	Crystalline Silica	14808-60-7

#### National Regulations Key

 $\sim$  Indicates a chemical listed by IARC as a possible carcinogen.

^ Indicates a chemical listed by IARC as carcinogenic to humans.



# RDINAL SAFETY DATA SHEET

**ISSUED:** 8/23/2018 **REFERENCE:** GR487-C241

#### **STATE REGULATIONS CALIFORNIA PROPOSITION 65**

This product contains:	Chemical CAS#
*Titanium Dioxide	13463-67-7
*Hydrated magnesium silicate	14807-96-6
*Crystalline Silica	14808-60-7
*Carbon Black	1333-86-4
*Diethanolamine	111-42-2

### **Proposition 65 Key**

WARNING: This product can expose you to a chemical(s), including those listed above, which is (are) known to the State of California to cause cancer.

For more information visit <u>WWWPROP65.CA.GOV</u>.

WARNING: This product can expose you to a chemical(s), including those listed above, which is (are) known to the State of California to cause birth defects or other reproductive harm.

For more information visit <u>WWWPROP65.CA.GOV</u>.

WARNING: This product can expose you to a chemical(s), including those listed above, which is (are) known to the

State of California to cause cancer and birth defects or other reproductive harm.

For more information visit WWWPROP65.CA.GOV.

### **Massachusetts Right to Know**

This product contains	Chemical CAS#
Limestone	1317-65-3
Titanium Dioxide	13463-67-7
Hydrated magnesium silicate	14807-96-6
Aluminum Oxide	1344-28-1
Amorphous Silica	112926-00-8
Crystalline Silica	14808-60-7
Carbon Black	1333-86-4
Diethanolamine	111-42-2

#### Pennsylvania Right to Know

This product contains	Chemical CAS#
Limestone	1317-65-3
Titanium Dioxide	13463-67-7
Hydrated magnesium silicate	14807-96-6
Aluminum Oxide	1344-28-1
Amorphous Silica	112926-00-8
Crystalline Silica	14808-60-7
Carbon Black	1333-86-4
Diethanolamine	111-42-2
Amorphous Pyrogenic Silica	112945-52-5



### **New Jersey Right to Know**

This product contains	Chemical CAS#
Limestone	1317-65-3
Titanium Dioxide	13463-67-7
Hydrated magnesium silicate	14807-96-6
Aluminum Oxide	1344-28-1
Amorphous Silica	112926-00-8
Crystalline Silica	14808-60-7
Carbon Black	1333-86-4
Diethanolamine	111-42-2
Amorphous Pyrogenic Silica	112945-52-5



# RDINAL SAFETY DATA SHEET

**ISSUED:** 8/23/2018 **REFERENCE:** GR487-C241

#### **16. OTHER INFORMATION**

# **Other Product Information:**

% Volatile by Volume: 0.03 % Volatile by Weight: 0.02 % Solids by volume: 99.98 % Solids by Weight: 99.98


# **VOC CONTENT:**

Content tested per EPA METHOD 24, ASTM D2369 is less than 1% Wt/Wt.

### **HMIS RATING**

Health :	2
Flammability :	1
Reactivity:	0
Personal Protection :	Е

# NFPA CODES



**MANUFACTURER DISCLAIMER:** The information contained in this Safety Data Sheet is considered to be true and accurate. Cardinal Paint and Powder makes no warranties, expressed or implied, as to the accuracy and adequacy of this information. This data is offered solely for the user's consideration, investigation and verification.