

SAFETY DATA SHEET



DATE ISSUED :	5/14/2016
SDS REF. No :	6SLA-200

6SLA-200 ANTI CRATERING ADDITIVE

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: 6SLA-200 VOC ANTI CRATERING ADDITIVE

PRODUCT CODE: 6SLA-200

PRODUCT USE: Industrial Paint Additive

MANUFACTURER

Cardinal Industrial Finishes
1329 Potrero Ave

S. El Monte, CA,
626 444-9274

24 HR. EMERGENCY TELEPHONE NUMBER

CHEMTREC (US Transportation): (800)424-9300

CHEMTREC (International : 1(202)483-7616

Transportation)

WEB: WWW.CARDINALPAINT.COM

2. HAZARDS IDENTIFICATION

PICTOGRAMS



SIGNAL WORD : DANGER

HAZARD STATEMENTS :

H226 Flammable liquid and vapor.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

PRECAUTIONARY STATEMENTS :

P233 Keep container tightly closed.

P241 Use explosion-proof electrical/ventilating/lighting/.../equipment.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P403 Store in a well-ventilated place.

P501 Dispose of in accordance with Local, Regional, State, Federal, and International Regulations.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	Weight %	CAS Number	
Acetone	75% - 80%	67-64-1	
P.M. Acetate	10% - 15%	108-65-6	

4. FIRST AID MEASURES

Description of first aid measures.

EYES CONTACT : EYE CONTACT: Can cause irritation and redness, tearing and blurred vision.

SKIN CONTACT : SKIN CONTACT: Moderate irritation possible from prolonged exposure; defatting and dermatitis.

INGESTION : INGESTION: Can cause gastrointestinal irritation, headache, dizziness, nausea and weakness.

INHALATION : INHALATION: May cause nasal irritation, headache, dizziness, nausea, weakness or vomiting. Loss of consciousness.

Most important symptoms and effects, both acute and delayed. Symptoms/injuries: Eye irritation

Symptoms/injuries after inhalation: May cause drowsiness or dizziness.

Symptoms/injuries after eye contact: Cause serious eye irritation.

Symptoms/injuries after ingestion: Ingestion may cause nausea, vomiting and diarrhea.

Indication of any immediate medical attention and special treatment needed.

If medical advise is needed, have product container or label on hand.

5. FIRE FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA : Foam, alcohol foam, CO₂, dry chemical, water fog.

FIRE FIGHTING PROCEDURE : Firefighting instructions: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering the environment.

Protection during firefighting: Firefighters should wear full protective gear. Do not enter fire area without proper protective equipment, including self-contained breathing apparatus with full face piece operated in pressure demand or other positive pressure modes.

UNUSUAL FIRE AND EXPLOSION HAZARD : Fire hazard: Highly flammable/liquid or vapor.

Explosive hazard: May form flammable/explosive vapor-air mixture.

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES :

General measures: Remove ignition sources. Use special care to avoid static electric charges. No smoking.

FOR NON-EMERGENCY PERSONNEL :

For non-Emergency procedures: Evacuate unnecessary personnel.

FOR EMERGENCY RESPONDERS :

Equip cleanup crew with proper protection. Avoid breathing fume, vapors.

ENVIRONMENTAL PRECAUTIONS :

Prevent entry to sewers and public waters.

METHODS AND MATERIAL FOR CONTAINMENT AND CLEAN UP :

BP_MCC

7. HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING : Additional hazards when processed: Handle empty containers with care because residual vapors are flammable.

Precautions for safe handling: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when you are leaving work. Provide good ventilation in process area to prevent formation of vapor. No smoking. Use only non-sparking tools. Use outdoors or in a well ventilated area. Avoid breathing fume, vapors.

Hygiene measures: Wash Skin thoroughly after handling.

CONDITIONS FOR SAFE STORAGE, INCLUDING INCOMPATIBILITIES : Storage conditions: Store in a dry, cool and well-ventilated place away from: Heat sources. Direct sunlight.

Incompatible products: Strong bases. Strong acids.

Incompatible materials: Source of ignition. Direct sunlight. Heat Sources.

8. EXPOSURE CONTROLS\PERSONAL PROTECTION

Acetone(67-64-1)		
USA ACGIH	ACGIH STEL TLV	750 ppm
USA ACGIH	ACGIH TWA TLV	500 ppm
USA NIOSH	NIOSH STEL (Table Z-1)	1,000 ppm, 2,400 mg/m ³

USA NIOSH	NIOSH TWA	250 ppm, 590 mg/m ³
USA OSHA	OSHA TWA (Table Z-1)	1,000 ppm, 2,400 mg/m ³
P.M. Acetate(108-65-6)		
USA AIHA	AIAH (WEEL) TWA	50 ppm

PERSONAL PROTECTIVE EQUIPMENT

RESPIRATORY PROTECTION : If TLV of the product or any component is exceeded, a NIOSH approved Air Supplied Respirator is advised in absence of environmental control. OSHA Regulations also permit other NIOSH Respirators under specified conditions. (See your Safety Equipment Supplier) Engineering or administrative controls should be implemented to reduce exposure.

HAND PROTECTION REMARKS : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

EYES PROTECTION : Wear OSHA approved chemical splash goggles. (Consult your safety equipment supplier)

SKIN AND BODY PROTECTION : Prevent repeated or prolonged skin contact with GB Protective Handcream, wear impervious clothing and chemical resistant boots.

WORK HYGIENIC PRACTICES: Wash hands before eating or using the rest room, smoke in smoking areas only.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	:	Liquid
Color	:	Various colors depending on the pigmentation.
Odor	:	Characteristic. Sweet. Mint like.
Odor threshold	:	No data available.
Ph	:	N/A - See Technical Data Sheet
Evaporation rate	:	Slower Than Ether
Melting point	:	-94.7 C (-138.46 F)
Freezing point	:	No data available.
Boiling point	:	133.0 deg F TO 294.0 deg F
Flash point	:	-4.00 deg F
Lower explosion limit	:	1.5
Upper explosion limit	:	12.8
Vapor pressure	:	185 mm Hg
Vapor density	:	Heavier than air
Relative density	:	No data available.
Density	:	7.0384
Solubility	:	No data available.
Partion coefficient: n-octanol/water	:	No data available.
Autoignition temperature	:	No data available.
Decomposition temperature	:	No data available.

10. STABILITY AND REACTIVITY

REACTIVITY : No dangerous reaction known under conditions of normal use.

CHEMICAL STABILITY : Stable.

CONDITIONS TO AVOID : Extremely high temperatures.

INCOMPATIBLE MATERIALS : Avoid contact with strong oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Hazardous decomposition may produce carbon dioxide and/or carbon monoxide.

11. TOXICOLOGICAL INFORMATION

Acetone(67-64-1)	
Aspiration toxicity	Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above TLV value may cause narcotic effects., Solvents may degrease the skin.
Carcinogenicity	Species: mouse, (female), Application Route: Dermal; Exposure time: .365 d (90%) or 424 d

	(100%), Dose: 0.1ml 90(71mg) or 100% (79mg), Frequency of Treatment: 3 times a wk, NOAEL: 79; Result: did not display carcinogenic properties., Carcinogenicity-Assessment: Not classified as a human carcinogen.
Germ cell mutagenicity	Test Type: mammalian cell gene mutation assay. Test species: Mouse Lymphoma, Metabolic activation: Without metabolic activation; Method: OECD Guideline 476; Result: negative; Test Type: Ames test, Metabolic activation: Without metabolic activation; Method: OECD Guideline 471; Result: negative, Test Type: Chromosome aberration test in vitro, Test species: Chinese hamster ovary (CHO), Metabolic activation: Without metabolic activation; Method: OECD Guideline 473; Result: negative; Genotoxicity in vivo: Test Type: I vivo micronucleus test. Test species: Mouse, Application Route: Oral, Exposure: 13 wk, Dose: 5,000, 10,000, 20,000 ppm, Result: negative
Germ cell mutagenicity Assessment	Animal testing did not show any mutagenic effects.
LC50 (rat) Inhalation	76 mg/l (4 h exposure)
LD50 (rat) Oral	5,800 mg/kg; Symptoms: tremors
LD50 Dermal	>7,426 mg/kg
Repeated dose exposure	Species: mouse, male, NOAEL: 20,000, Application Route: Oral, Exposure time: 13 wk, Number of exposures: daily, Dose: 1250, 2500, 5000, 10000, 20000, Method OECD Test Guideline 408, GLP: No data available.; Species: mouse, female, NAOEL 20000, LAOEL: 50000; Application Route: Oral, Exposure time: 13 wk, Number of exposures: daily, Dose: 1250, 2500, 5000, 10000, 20000, Method OECD Test Guideline 408, GLP: No data available; Repeated dose toxicity Assessment: causes mild skin irritation., Causes serious eye irritation.
Reproductive toxicity	Effects on fertility: Species: rat, male; Application Route: oral; Dose: 0, 5,000, 10,000 mg/l; Frequency of Treatment: 7 days/week; General Toxicity - Parent: LOAEL: 10,000; Fertility: 10,000; Effects on fetal development: Species: rat; Application Route: Inhalation; Dose: 0, 440, 2200, 11,000 ppm; Frequency of Treatment: 7 days/week; General Toxicity Material: NOAEC: 2,200 ppm; Tetrageicity: NOAEC: 2,200 ppm; Embryo-fetal toxicity:: NOAEC: 2,200 ppm; Result: No teratogenic potential. GLP: No data available.; Reproductive toxicity Assessment: Did not show teratogenic effects in animal experiments.
Respiratory or skin sensitisation	Test type: Maximization test, Species: guinea pig, Assessment: Does not cause skin sensitization. Result: Did not cause sensitization on laboratory animals.
Serious eye damage/eye irritation	Species: rabbit, Result : Slightly irritating to eyes, Exposure time: 24 h, Classification: Irritating to eyes, Remarks: Eye irritation.
Skin corrosion/irritation	Species: rabbit, Exposure time: 24 h, Classification: Not irritating to skin, Method: In vivo, Result: Mild irritation, Remarks: Repeated or prolonged contact with the mixture may cause removal natural fat from the skin resulting in desiccation of the skin.
STOT - single exposure	Exposure routes: Inhalation (vapor); Assessment: May cause drowsiness or dizziness.
STOT- repeated exposure	No data available.
P.M. Acetate(108-65-6)	
Aspiration hazard	No data available.
Carcinogenicity	No data available.
LC50 - Inhalation Rat	>4345 ppm (Rat, 6 h)
LD50 - Dermal - Rabbit	>5000 mg/kg
LD50 - Oral - Rat	6,190 mg/kg
Mutagenicity	In vitro: No data available. In vivo: No data available.
Other adverse effects	No data available.
Repeated dose toxicity	No data available.
Reproductive toxicity.	No data available.
Respiratory or skin sensitization	Skin Sensitization:, (Guinea Pig) - non-sensitizing
Serious eye damage/eye irritation	(Rabbit): very slight
Skin corrosion/irritation	Specified substance(s) 2-methoxy-1-methylethyl acetate (Rabbit, 4 h): none (Rabbit, 24 h): none.
Specific target organ toxicity - repeated exposure	No data available.
Specific target organ toxicity - single exposure	No data available.

12. ECOLOGICAL INFORMATION

Acetone(67-64-1)	
Bioaccumulative potential	Partition coefficient: n-octanol/water: log Pow: -0.24
EC50 (Daphnia magna (Water flea))	7,630 mg/l (Exposure time 48 h); Test substance: Acetone
LC50 (Oncorhynchus)	6,100 mg/l (Exposure time: 48 h)

mykiss (rainbow trout))	
Mobility in soil	No data available.
Other adverse effects	No data Available. Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances., Additional ecological information: No data available.
Persistence and degradability	Biodegradability: Remarks: No data available
Toxicity to algae	Remarks: No data available
P.M. Acetate(108-65-6)	
Aquatic invertebrates	NOEC (daphnia, 21 d): >= 100 mg/l EC-50 (daphnia, 21 d): > 100 mg/l
Bioaccumulative potential	No data available.
Biological Oxygen Demand	363 mg/g 1,050 mg/g
Chemical Oxygen Demand	No data available.
Chronic Toxicity Fish	LC-50 (Oryzias latipes, 14 d): 63.5 mg/l NOEC (Oryzias latipes, 14 d): 47.5 mg/l
LC50 - Daphnoid - Aquatic invertebrates	408 mg/l (48 h)
LC50 - Fathead Minnow - Toxicity to Fish	161 mg/l (96 h)
Mobility in soil	No data available.
Other adverse effects	No data available.
Persistence and degradability	Biodegradation - 90 % (28 d, Ready Biodegradability: CO2 Evolution Test) Readily biodegradable
Results of PBT and vPvB assessment	No data available.
Toxicity to Aquatic Plants	EC-50 (Senastrum capricornutum, 96 h): > 1,000 mg/l NOEC (Senastrum capricornutum, 96 h): >= 1,000 mg/l

13. DISPOSAL CONSIDERATIONS

WASTE TREATMENT METHODS

GENERAL INFORMATION : No data available.

DISPOSAL METHOD: Recycle whenever possible or destroy by liquid incineration in accordance with applicable regulations. Contaminated absorbent should be incinerated or sent to an approved landfill in accordance with Local, State, and Federal Regulations.

14. TRANSPORT INFORMATION

***CHECK WITH YOUR CARRIER FOR ADDITIONAL RESTRICTIONS THAT MAY APPLY.**

USDOT GROUND

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME (DOT) : Paint Related Material

HAZARDS CLASS : 3

UN/NA NUMBER : UN1263

PACKING GROUP : PG II

EMERGENCY RESPONSE GUIDE (ERG) : 128

IATA (AIR)

DOT (INTERNATIONAL AIR TRANSPORTATION ASSOCIATION)

PROPER SHIPPING NAME : Paint, flammable liquid

HAZARDS CLASS : 3

UN/NA NUMBER : UN1263

PACKING GROUP : PG II

EMERGENCY RESPONSE GUIDE (ERG) : 128

IMDG (OCEAN)

PROPER SHIPPING NAME : Paint, flammable liquid

HAZARDS CLASS : 3

UN/NA NUMBER : UN1263

PACKING GROUP : PG II

EMERGENCY RESPONSE GUIDE (ERG) : 128

MARINE POLLUTANT : No

SPECIAL PRECAUTIONS : P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking. P235 Keep cool.

15. REGULATORY INFORMATION

US FEDERAL REGULATIONS

All ingredients in Section #3 are TSCA (Toxic Substance Control Act) listed.

OSHA HAZARDS : Flammable liquid, Moderate skin irritant, Moderate eye irritant, Carcinogen.

EPCRA - Emergency

CERCLA REPORTABLE QUANTITY

SARA 304 Extremely Hazardous Substances Reportable Quantity : This material does not contain any components with a section 304 EHS RQ.

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

SARA 311/312 Hazards : Fire Hazard, Acute Health Hazard, Chronic Health Hazard

SARA 313 :

This product contains:	Chemical CAS#
Acetone	67-64-1
P.M. Acetate	108-65-6

CLEAN AIR ACT :

INTERNATIONAL REGULATIONS

CLASSIFICATION ACCORDING TO REGULATION (EC) No. 1272/2008 (CLP) :

Flam. Liq. Cat. 2; H226
Skin Sens. Cat. 1; H317
Acute Tox. Inhalation, Cat. 4; H332
STOT SE, Inhalation, Cat. 3; H335

NATIONAL REGULATIONS

Indicates a chemical listed by IARC as a possible carcinogen.

STATE REGULATIONS

CALIFORNIA PROPOSITION 65

*This product contains (a) chemical (s) known to the State of California to cause cancer.

#This product contains (a) chemical (s) known to the State of California to be carcinogenic.

+This product contains (a) chemical (s) known to the State of California to cause birth defects or other reproductive harm.

Massachusetts Right to Know

This product contains	Chemical CAS#
Acetone	67-64-1

Pennsylvania Right to Know

This product contains	Chemical CAS#
Acetone	67-64-1
P.M. Acetate	108-65-6

New Jersey Right to Know

This product contains	Chemical CAS#
Acetone	67-64-1

P.M. Acetate	108-65-6
--------------	----------

16. OTHER INFORMATION

Other Product Information


% Volatile by Volume: 90.49	% Volatile by Weight: 87.00
% Solids by volume: 9.51	% Solids by Weight: 13.00
% Exempt by Volume: 80.01	% Exempt by Weight: 75.00

VOC CONTENT: Excluding Exempt VOC: 506
 Including Exempt VOC: 101

HMIS RATING

Health :	2
Flammability :	3
Reactivity :	0
Personal Protection :	H

NFPA CODES



MANUFACTURER DISCLAIMER : The information contained in this Safety Data Sheet is considered to be true and accurate. Cardinal Industrial Finishes makes no warranties, expressed or implied, as to the accuracy and adequacy of this information. This data is offered solely for the user's consideration, investigation and verification.